

Chemtrec: 800-424-9300

Rev. 0, 1/27/2016

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: FastenMaster FLEX 180

Supplier and OMG, Inc. 24-hour Emergency Response Number:

Responsible 153 Bowles Road

Party: Agawam, MA 01001 USA

Phone: (01) 413-789-0252 Fax: (01) 413-786-1453 www.fastenmaster.com

Product Use(s): Industrial hot melt adhesive

2. HAZARDS IDENTIFICATION

Classification(s): None applicable Symbol(s): None applicable Signal Word(s): None applicable

Hazard No

None applicable

Statement(s):

Precautionary None applicable

Statement(s):

3. COMPOSITION/INFORMATION ON INGREDIENTS

This formula of this product is a Trade Secret. No ingredients of the product are classified as *Health Hazards* or *Physical Hazards* per U.S. HAZCOM regulations (29CFR 1910.1200) or Canada's *Hazardous Products Regulations* (SOR/DORS/ 2015-17).

4. FIRST AID MEASURES

Eyes: If eyes contact molten product, immediately flush with water for at least fifteen

minutes. Do not attempt removal of product from eyes. Seek immediate

medical assistance.

Skin: If molten product contacts skin, drench with water for at least five minutes.

Cover with gauze and seek immediate medical assistance. Do not attempt

removal of product from skin.

Ingestion: Ingestion of solid product may cause nausea and gastrointestinal irritation.

Inhalation: If exposed to fumes of decomposition from overheating the product, remove

subject to fresh air and keep comfortable for breathing. Seek medical attention

if necessary. Keep the subject warm and at rest.

Guidance for Physician or Poison Control Center: None of the components of this product are acutely toxic by ingestion or inhalation. Eye contact with molten product can cause severe injury. Skin contact with molten product can cause skin burns. Ingestion is unlikely to occur in industrial use, but if ingestion occurs it may cause nausea and

gastrointestinal irritation.

FastenMaster FLEX 180 Page 1 of 5



Rev. 0, 1/27/2016

5. FIREFIGHTING MEASURES

Extinguishing Media: Use dry chemical or carbon dioxide. DO NOT use water.

Fire and Explosion

Hazards:

This product is nonflammable and noncombustible. If present in a fire or explosion, potential thermal decomposition byproducts include

smoke, carbon monoxide, and irritant decomposition byproducts.

Firefighting Instructions: If fighting a fire in which this product is present, wear a self-contained

breathing apparatus with full-facepiece operated in pressure-demand

or other positive pressure mode.

6. ACCIDENTAL RELEASE MEASURES

Methods and Materials: Clean up spilled product for reuse or disposal. If molten product is

spilled, allow to cool and solidify before handling.

Personal Precautions: No special personal precautions are required.

Environmental Precautions:

Prevent product from entering sewers or contaminating soil.

7. HANDLING AND STORAGE

Handling Precautions: No special handling precautions are required.

Work and Hygiene

Storage Precautions:

Practices:

As good hygiene practice following use of the product, wash hands and face before eating, drinking, or using cosmetics or tobacco.

Store below 120°F. (50°C.) and away from incompatible materials

(see Section #10).

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ingredients Exposure

Limits:

There are no OSHA Permissible Exposure Limits or ACGIH Threshold

Limit Values for any ingredients of the product.

Ingredients Biological

Limits:

There are no ACGIH Biological Exposure Indices or other biological

limits for any ingredients of the product.

Engineering Controls: Local exhaust ventilation is not required when using this product in

accordance with instructions.

Eye/Face Protection: Wear eye protection adequate to prevent eye contact with the product.

Plastic-frame spectacles with side shields or chemical goggles are recommended. If spraying or splashing of product is possible, wear

a face shield.

Skin Protection: Wear protective gloves and clothing to prevent injury from skin contact

with molten product.

Respiratory Protection: If a respirator is worn for comfort, use of a NIOSH-approved respirator

is recommended. Consult the specific OSHA regulations (29CFR1910.134) and/or American National Standard Z88.2 (ANSI,

New York, NY 10036, USA) for guidance.

FastenMaster FLEX 180 Page 2 of 5



Rev. 0, 1/27/2016

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: light yellow solid Lower/Upper Explosive Limits: not determined

Odor: faint

Odor threshold: not determined

pH: not applicable

Evaporation Rate: not applicable Percentage VOCs: not determined Melting point: approx. 175°F./79°C. Relative density (H₂O): not determined Freezing point: not determined

Boiling point/Boiling range: not determined

Flash Point: >500°F./260°C. Autoignition Point: not determined Flammability Class: not applicable Solubility (H₂O): insoluble Oil-water partition coefficient: not determined

Vapor pressure: not applicable

Vapor density: not applicable

Decomposition temperature: not determined Viscosity: approx. 4,500 cps @ 350°F./177°C.

10. STABILITY AND REACTIVITY

Stability and Reactivity: Stable and non-reactive

Conditions to Avoid: Product should not be heated above 400°F./204°C.

Hazardous Polymerization: Will not occur Incompatible Materials: Oxidizing agents

Potential Decomposition Carbon monoxide, carbon dioxide, smoke, and irritant

Byproducts: decomposition byproducts

11. TOXICOLOGICAL INFORMATION

Ingredient Toxicology Data: No toxicology data is available for any of the ingredients via any

route of exposure.

Primary Route(s) of Entry: Ingestion

Eve Hazards: In molten form, this product can cause severe eye injury.

Skin Hazards: In molten form, this product may cause skin burns.

Ingestion Hazards: The product is nontoxic by ingestion.

Inhalation Hazards: Inhalation of toxicologically-significant quantities of ingredients is

unlikely when the product is used in accordance with instructions.

Symptoms Related to

Overexposure:

None reasonably foreseeable.

Delayed Effects from

Long Term Overexposure:

None reasonably foreseeable.

Carcinogenicity: No ingredients are classified as potential or confirmed human

carcinogens by OSHA, NTP, or IARC.

Germ Cell Mutagenicity: No ingredients have been determined to be germ cell mutagens.

Reproductive Toxicity: No ingredients have been determined to be damaging to fertility or

to the unborn child.

Acute Toxicity Estimates: No data available via ingestion, inhalation, or dermal contact.

Interactive Effects of

Ingredients:

No data available.

FastenMaster FLEX 180 Page 3 of 5



Rev. 0, 1/27/2016

12. ECOLOGICAL INFORMATION

Ecotoxicity: No ecotoxicity data are available for the product or its components.

Ozone Depletion This product neither contains nor is manufactured with any ingredients

Potential: known to deplete the ozone layer.

13. DISPOSAL CONSIDERATIONS

Do not discharge waste product into sanitary or storm sewers or allow it to contaminate soil. Consult applicable Federal, State/Provincial, and local regulations.

14. TRANSPORTATION INFORMATION

Transport of the product is not regulated by USDOT, TDG (Canada), IATA, or IMO.

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA Information: All ingredients of this product are listed in the TSCA Registry.

SARA Hazard None applicable.

Classes:

EPCRA Section This product contains no ingredients in concentrations ≥1% (≥0.1% for

313 Notification: carcinogens) regulated under Section 313 of the *Emergency Planning and*

Community Right-To-Know Act of 1986 or 40 CFR 372.

Canadian Regulatory Information

This product has been classified in accordance with Canada's *Hazardous Products Regulations* (SOR/DORS/2015-15).

16. OTHER INFORMATION

Hazardous Materials Health Flammability Physical Hazard PPE Information System (III) 0 1 0 See Note

Ratings (Legend): (minimal hazard) (slight hazard) (minimal hazard)

Note regarding PPE: OMG, Inc. recommends use of protective eyewear and skin protection

(Personal Protection Index "B") as standard PPE for the anticipated conditions of use of this product. However, HMIS recommends that its ratings be used only in conjunction with a fully implemented HMIS program, and that specific PPE codes should be created by the user, who is familiar with the actual conditions under which the product is used. We cannot anticipate every condition of the product's use, and it is the user's responsibility to evaluate the hazards pertinent to its specific operations, and to determine the specific PPE required.

National Fire Protection Health Speciation (NFPA) Health Flammability Reactivity 0 1 0

Ratings:

FastenMaster FLEX 180 Page 4 of 5



Rev. 0, 1/27/2016

16. OTHER INFORMATION (continued)

Revision Information: Publication Date: 27 January 2016

Date of Prior SDS: not applicable

DISCLAIMER

Our products and the information contained herein are supplied on the condition that the persons receiving same will make their own determination as to suitability for their purposes prior to use. In no event will OMG be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information from this sheet or the products to which the information refers. OMG does not warrant the accuracy or timeliness of the information in this sheet and has no liability for any errors or omissions in these materials. **The information contained in this SDS was provided by a third party to OMG.**

THIS SHEET IS PROVIDED ON AN "AS IS" BASIS. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION PROVIDED OR THE PRODUCTS TO WHICH THE INFORMATION REFERS.

FastenMaster FLEX 180 Page 5 of 5